AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

- 1-20. (Canceled).
- 21. (New) A dishwasher, comprising:
- a tub for accommodating dishes for washing;
- a sump housing receiving water for dishwashing, the sump housing coupled to a bottom of the tub;
- a wash motor mounted to an outer bottom surface of the sump housing and having a motor shaft extended into the sump housing by passing through the outer bottom surface of the sump housing from the wash motor;
 - a wash pump located within the sump housing, the wash pump including:
 - a pump case; and
- an impeller for pumping the water for dishwashing within the pump case, wherein the impeller is connected to an end of the motor shaft;
 - a sealing case upwardly extended from an inner bottom surface of the sump housing;
 - a sealing cover fitted within the sealing case and penetrated by the motor shaft; and
- an air cap covering the sealing case and the sealing cover and penetrated by the motor shaft, wherein the air cap has a space therein for accommodating air in order to prevent the water for dishwashing from being drawn into the sealing case.
 - 22. (New) The dishwasher according to claim 21, wherein the air cap includes: an upper plate;
- a motor shaft through-sleeve extending upward by a predetermined diameter and height from the upper plate, the motor shaft through-sleeve surrounding the motor shaft to be in close contact with the outer surface of the motor shaft;
 - an outer wall extending downward from an edge of the upper plate; and

Docket No. 9988.301.00

Application No. 10/568,221 Amendment dated June 23, 2009 Reply to Office Action dated March 23, 2009

an inner wall extending downward from the bottom surface of the upper plate,

wherein the inner wall is defined within the outer wall by being a predetermined distance away from the outer wall.

- 23. (New) The dishwasher according to claim 22, wherein end portions of the outer wall and the inner wall are respectively a predetermined distance away from the inner bottom surface of the sump housing such that air and the water for dishwashing are drawn into the air cap.
- 24. (New) The dishwasher according to claim 22, wherein the sealing case is configured to be received in the space defined by the inner wall of the air cap.
- 25. (New) The dishwasher according to claim 21, wherein the sealing cover is bent downward to be in close contact with the inner bottom of the sump housing, and has a space therein to receive sealing oil.
- 26. (New) The dishwasher according to claim 25, wherein an inner circumference of the sealing cover, which is in contact with the motor shaft, has a plurality of sealing lips which are firmly pressed to the outer surface of the motor shaft, in order to block off the water for washing into the sealing cover.